


METRIC CONDUIT THREAD (PG SERIES)

Ref: DIN 40430 - 1971



LIMITS

NOM. SIZE	PITCH	THREADS PER INCH	EXTERNAL THREAD						INTERNAL THREAD					
			MAJOR DIA.		PITCH DIA.		MINOR DIA.		MAJOR DIA.		PITCH DIA.		MINOR DIA.	
			max.	min.	max.	min.	max.	min.	min.	max.	min.	max.	min.	max.
PG 7	1.27	20	12.5	12.3	11.89	11.69	11.28	11.08	12.5	12.65	11.89	12.04	11.28	11.43
PG 9	1.41	18	15.2	15	14.53	14.33	13.86	13.66	15.2	15.35	14.53	14.68	13.86	14.01
PG 11	1.41	18	18.6	18.4	17.93	17.73	17.26	17.06	18.6	18.75	17.93	18.08	17.26	17.41
PG 13.5	1.41	18	20.4	20.2	19.73	19.53	19.06	18.86	20.4	20.55	19.73	19.88	19.06	19.21
PG 16	1.41	18	22.5	22.3	21.83	21.63	21.16	20.96	22.5	22.65	21.83	21.98	21.16	21.31
PG 21	1.588	16	28.3	28	27.54	27.24	26.78	26.48	28.3	28.55	27.54	27.79	26.78	27.03
PG 29	1.588	16	37	36.7	36.24	35.94	25.48	35.18	37	37.25	36.24	36.49	35.48	35.73
PG 36	1.588	16	47	46.7	46.24	45.94	45.48	45.18	47	47.25	46.24	46.49	45.48	45.73
PG 42	1.588	16	54	53.7	53.24	52.94	52.48	52.18	54	54.25	53.24	53.49	52.48	52.73
PG 48	1.588	16	59.3	59	58.54	58.25	57.78	57.48	59.3	59.55	58.54	58.79	57.78	58.03